



# FORCE AND PRESSURE TESTS ON A SEMI-SPAN DELTA WING AT SUPERSONIC SPEEDS

Larry J. Pfaff

ARO, Inc.

PROPERTY OF U. S. AIR FORCE  
AEDC LIBRARY  
AF 40(600)1200

August 1965

This document has been approved for public release  
its distribution is unlimited.

Per ASDC-TR-1515  
AD 11 700  
D + d July 1975

**VON KÁRMÁN GAS DYNAMICS FACILITY  
ARNOLD ENGINEERING DEVELOPMENT CENTER  
AIR FORCE SYSTEMS COMMAND  
ARNOLD AIR FORCE STATION, TENNESSEE**

AEDC TECHNICAL LIBRARY



5 0720 00031 1151

# ***NOTICES***

When U. S. Government drawings specifications, or other data are used for any purpose other than a definitely related Government procurement operation, the Government thereby incurs no responsibility nor any obligation whatsoever, and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data, is not to be regarded by implication or otherwise, or in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Qualified users may obtain copies of this report from the Defense Documentation Center.

References to named commercial products in this report are not to be considered in any sense as an endorsement of the product by the United States Air Force or the Government.

FORCE AND PRESSURE TESTS ON A SEMI-SPAN  
DELTA WING AT SUPERSONIC SPEEDS

Larry J. Pfaff  
ARO, Inc.

This document has been approved for public release  
its distribution is unlimited. Per DPC TR-75/5  
AD A011 700  
Dtd July 1975

## FOREWORD

The work reported herein was done at the request of the Air Force Office of Scientific Research (AFOSR) for Aerospace Research Associates (ARA), under Program Element 61445014/9781, Task 978101.

The results of tests presented were obtained by ARO, Inc. (a subsidiary of Sverdrup and Parcel, Inc.), contract operator of the Arnold Engineering Development Center (AEDC), Air Force Systems Command (AFSC), Arnold Air Force Station, Tennessee, under Contract AF 40(600)-1200. The tests were conducted on May 6 and 7, 1965 under ARO Project No. VA0545, and the manuscript was submitted for publication on July 8, 1965.

This technical report has been reviewed and is approved.

Darrel K. Calkins  
Major, USAF  
AF Representative, VKF  
DCS/Test

Jean A. Jack  
Colonel, USAF  
DCS/Test

**ABSTRACT**

Static-force and pressure tests were conducted in the 40-in. supersonic tunnel of the von Kármán Gas Dynamics Facility on a 70-deg, blunt leading-edge, semi-span delta wing. The wing consisted of three sections, triangular forward and tip panels and a rectangular main panel. Tests were made with the forward panel deflected -2.5 deg and undeflected (flat wing). Force data on the total wing and pressure data on the tip panel were obtained at Mach numbers from 3 to 5; additional pressure data were obtained at Mach number 6. The angle-of-attack range was from -4 to 10 deg, and Reynolds number, based on the wing root chord, ranged from  $9 \times 10^6$  at Mach number 3 to  $18 \times 10^6$  at Mach number 6. Wing lift-to-drag ratio and tip panel pressure data are presented for the wing with the forward panel deflected and undeflected.

## CONTENTS

	<u>Page</u>
ABSTRACT . . . . .	iii
NOMENCLATURE . . . . .	v
I. INTRODUCTION . . . . .	1
II. APPARATUS	
2.1 Wind Tunnel . . . . .	1
2.2 Models and Model Support . . . . .	1
2.3 Instrumentation and Techniques . . . . .	2
III. RESULTS AND DISCUSSION . . . . .	3
REFERENCES . . . . .	4

## ILLUSTRATIONS

Figure

1. Model Details	
a. Force Model . . . . .	5
b. Pressure Model . . . . .	6
2. General Arrangement of the Sidewall Angle-of-Attack Mechanism and Model Support Details . . . . .	7
3. Installation Photograph . . . . .	8
4. Model Photographs . . . . .	9
5. Variation of $L/D$ with Angle of Attack at $M_\infty = 3$ and 5 . . . . .	10
6. Variation of $(L/D)_{\max}$ and Angle of Attack at $(L/D)_{\max}$ with Mach Number . . . . .	11
7. Pressure Distribution over Tip Panel for $M_\infty = 3$ and 5	
a. $\alpha = 6$ deg . . . . .	12
b. $\alpha = 10$ deg . . . . .	13

## NOMENCLATURE

$L/D$	Lift-to-drag ratio
$M_\infty$	Free-stream Mach number
$p$	Model surface pressure, psia

$P_0$	Stilling chamber pressure, psia
$P_\infty$	Free-stream static pressure, psia
$Re$	Reynolds number based on wing root chord
$\alpha$	Wing angle of attack, deg

#### MODEL NOMENCLATURE

F	Forward wing panel
T	Tip wing panel
W	Main wing panel

## SECTION I INTRODUCTION

Static-force and pressure tests were conducted for Aerospace Research Association (ARA) on models of a 70-deg, blunt leading-edge, semi-span delta wing in the 40-in., supersonic tunnel (Gas Dynamic Wind Tunnel, Supersonic (A)), of the von Kármán Gas Dynamics Facility (VKF). The models were mounted on a sidewall pitch drive mechanism, and data were obtained with the wing surface flat and with the forward panel deflected -2.50 deg. Force tests had previously been conducted in VKF on these configurations (Ref. 1). In the current tests the angle-of-attack range was extended to determine the angle of attack for maximum L/D, and pressure distributions were obtained on the tip panel.

Data were obtained at Mach numbers 3.0, 4.0, 4.5, and 5.0 at angles of attack from -4 to 10 deg, and additional pressure data were obtained at Mach number 6.0 for the same angle-of-attack range. The dynamic pressure was constant at 2.6 psia, which corresponds to a Reynolds number range, based on the wing root chord, of  $9 \times 10^6$  at  $M_\infty = 3$  and  $18 \times 10^6$  at  $M_\infty = 6$ .

## SECTION II APPARATUS

### 2.1 WIND TUNNEL

Tunnel A is a continuous, closed-circuit, variable density wind tunnel with an automatically driven flexible plate nozzle and a 40- by 40-in. test section. The tunnel operates at Mach numbers from 1.5 to 6 at maximum stagnation pressures from 29 to 200 psia, respectively, and stagnation temperatures up to 300°F ( $M_\infty = 6$ ). Minimum operating pressures are about one-tenth of the maximum at each Mach number. A description of the tunnel and airflow calibration information may be found in Ref. 2.

### 2.2 MODELS AND MODEL SUPPORT

The models supplied by ARA (Fig. 1) were constant thickness (1.5-in.), semi-span delta wings having hemispherical leading edges, a sweep-back angle of 70 deg, and a root chord of 48 in. Each model consisted of two triangular sections and a rectangular section. Each of



the two triangular panels, which comprised the forward and tip regions of the wing, had a root chord of 24 in. The surface area of each triangular panel was therefore 25 percent of the wing area, and the rectangular or main wing panel comprised 50 percent of the wing area. For the pressure tests the tip panel was instrumentated as shown in Fig. 1b.

A sectional view showing the sidewall-mounted angle-of-attack mechanism and the support for the three wing panels is presented in Fig. 2, and a tunnel installation photograph is presented in Fig. 3. Photographs of the two configurations tested are shown in Fig. 4. A description of the angle-of-attack mechanism is given in Ref. 1.

As shown in Fig. 2 the forward and tip wing panels were mounted on dummy balances which were in turn supported by the main wing balance through panel W. The forces and moments measured by the balance were therefore the aerodynamic loads on the total wing. The model was mounted in the same manner during the pressure phase of the tests.

Perfect alignment of the model panels could not be achieved because the weights of the solid steel panels caused deflection of the balances and support equipment. For example, in the case of configuration 1 the tip panel was slightly lower than the main panel, and a small longitudinal step existed on the wing surface. Alignment of the forward panel, accomplished by maintaining a smooth junction between the forward and main wing panels, resulted in an angular misalignment of these panels in pitch of  $-0.05$  deg. Panel alignment was further affected by aerodynamic loading, which not only altered the initial deflections but also introduced a lateral step on the wing surface between the forward and main wing panels. Similar initial misalignment of the wing panels of configuration 2 was minimized in the manner described above, and in all cases the smoothest possible wing surface was maintained.

### 2.3 INSTRUMENTATION AND TECHNIQUES

Total wing force measurements were made with a six-component, force-type, strain-gage balance supplied and calibrated by VKF. After the test a range of static loadings was applied to the balance which simulated the range of model loadings obtained during the test. These static loadings were applied in combinations to the balance components of interest. Listed below are the balance design loads and the range of static loadings applied to each component. The range of uncertainties

listed here corresponds to the differences between the applied loads and the values calculated by the balance equations used in the final data reduction.

<u>Balance Component</u>	<u>Design Load</u>	<u>Range of Static Loadings</u>	<u>Range of Uncertainties</u>
Normal force, lb	1200	75 to 250	$\pm 0.30$ to $\pm 1.40$
Pitching moment, in. -lb	800	320 to 560	$\pm 0.10$ to $\pm 1.30$
Side force, lb	100	25 to 50	$\pm 0.02$ to $\pm 0.35$
Yawing moment, in. -lb	3000	75 to 420	$\pm 0.25$ to $\pm 1.50$
Rolling moment, in. -lb	3400	600 to 2000	$\pm 1.00$ to $\pm 5.00$
Axial force, lb	1200	10 to 50	$\pm 0.20$ to $\pm 2.50$

Model surface pressures were measured with the standard pressure-scanning system of Tunnel A. This system utilizes 15-psid transducers referenced to a near vacuum. These transducers are calibrated for ranges of 15, 5, and 1 psia, and the precision of the system is estimated to be within 0.2 percent of full scale of the range being used.

The angle of attack is considered to be correct to within  $\pm 0.1$  deg, and the centerline flow uniformity is within  $\pm 0.5$  percent in Mach number.

Data on both configurations were obtained at the test conditions listed below.

<u><math>M_\infty</math></u>	<u><math>p_0</math>, psia</u>	<u><math>Re \times 10^{-6}/in.</math></u>
3.0	15.0	0.18
4.0	35.0	0.25
4.5	53.0	0.30
5.0	80.0	0.30
6.0	157.0	0.37

### SECTION III RESULTS AND DISCUSSIONS

Since the primary objective of the force tests was to determine the angle of attack for maximum  $L/D$ , only these results are presented.

Force and moment data were obtained on these configurations in previous tests and are available (up to  $\alpha = 6$  deg) in Ref. 1.


In Fig. 5 the variation of  $L/D$  with angle of attack at  $M_\infty = 3$  and 5 is given for both configurations. The data show that deflecting the forward panel -2.5 deg decreased  $L/D$  near zero angle of attack but had no significant effect at the higher angles of attack ( $\alpha > 6$  deg).

Figure 6 presents the variations with Mach number of maximum  $L/D$  and the angle of attack at  $(L/D)_{\max}$ . In general for both configurations  $(L/D)_{\max}$  decreased and the angle of attack at  $(L/D)_{\max}$  increased with increased Mach number. Deflecting the forward panel had no appreciable effect on  $(L/D)_{\max}$  or on the angle of attack at  $(L/D)_{\max}$  over the Mach number range.


In Figs. 7a and b pressure distributions on the bottom surface and along the leading edge of the tip panel are shown for angles of attack of 6 and 10 deg for  $M_\infty = 3$  and 5. As can be seen there were no significant effects of deflecting the forward flap -2.5 deg.

#### REFERENCES

1. Coats, Jack D. and Morgan, L. A. "Force Tests on Flat, Cambered, and Twisted Wings at Mach Numbers 3, 4, and 6." AEDC-TN-61-147 (AD326853), November 1961.
2. Test Facilities Handbook (Fifth Edition). "von Kármán Gas Dynamics Facility, Vol. 4." Arnold Engineering Development Center, July 1963.




All Dimensions in Inches



a. Force Model

Fig. 1 Model Details



b. Pressure Model

Fig. 1 Concluded




Fig. 2 General Arrangement of the Sidewall Angle-of-Attack Mechanism and Model Support Details




Fig. 3 Installation Photograph






Fig. 4 Model Photographs



Fig. 5 Variation of  $L/D$  with Angle of Attack at  $M_\infty = 3$  and 5






Fig. 6 Variation of  $(L/D)_{\max}$  and Angle of Attack at  $(L/D)_{\max}$  with Mach Number



$\alpha = 6^\circ$

Fig. 7 Pressure Distribution over Tip Panel for  $M_\infty = 3$  and 5


b.  $\alpha = 10$  deg

Fig. 7 Concluded

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1 ORIGINATING ACTIVITY (Corporate author) Arnold Engineering Development Center, ARO, Inc., Operating Contractor, Arnold Air Force Station, Tennessee		2a REPORT SECURITY CLASSIFICATION UNCLASSIFIED	
		2b GROUP N/A	
3 REPORT TITLE FORCE AND PRESSURE TESTS ON A SEMI-SPAN DELTA WING AT SUPERSONIC SPEEDS			
4 DESCRIPTIVE NOTES (Type of report and inclusive dates) N/A			
5 AUTHOR(S) (Last name, first name, initial) Pfaff, Larry J., ARO, Inc.		This document has been approved for public release its distribution is unlimited. <i>Per DDC-1772-15/5</i> <i>AD 1911 100</i> <i>12 July 1975</i>	
6 REPORT DATE August 1965	7a. TOTAL NO. OF PAGES 19	7b NO. OF REFS 2	
8a. CONTRACT OR GRANT NO. AF40(600)-1200	9a. ORIGINATOR'S REPORT NUMBER(S) AEDC-TR-65-165		
b. PROJECT NO. 9781			
c. Program Element 61445014			
d Task 978101	9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report) N/A		
10. AVAILABILITY/LIMITATION NOTICES Qualified requesters may obtain copies of this report from DDC.			
11. SUPPLEMENTARY NOTES N/A		12. SPONSORING MILITARY ACTIVITY Air Force Office of Scientific Research, Air Force Systems Command, Washington, D. C.	
13 ABSTRACT <p>Static-force and pressure tests were conducted in the 40-in. supersonic tunnel of the von Kármán Gas Dynamics Facility on a 70-deg, blunt leading-edge, semi-span delta wing. The wing consisted of three sections, triangular forward and tip panels and a rectangular main panel. Tests were made with the forward panel deflected -2.5 deg and undeflected (flat wing). Force data on the total wing and pressure data on the tip panel were obtained at Mach numbers from 3 to 5; additional pressure data were obtained at Mach number 6. The angle-of-attack range was from -4 to 10 deg, and Reynolds number, based on the wing root chord, ranged from <math>9 \times 10^6</math> at Mach number 3 to <math>18 \times 10^6</math> at Mach number 6. Wing lift-to-drag ratio and tip panel pressure data are presented for the wing with the forward panel deflected and undeflected.</p>			

14 KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
delta wings						
static-force tests						
pressure tests						
supersonic flow						

### INSTRUCTIONS

**1. ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (corporate author) issuing the report.

**2a. REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

**2b. GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

**3. REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

**4. DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

**5. AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

**6. REPORT DATE:** Enter the date of the report as day, month, year, or month, year. If more than one date appears on the report, use date of publication.

**7a. TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

**7b. NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

**8a. CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

**8b, &c, & 8d. PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

**9a. ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

**9b. OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (either by the originator or by the sponsor), also enter this number(s).

**10. AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through \_\_\_\_\_."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through \_\_\_\_\_."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through \_\_\_\_\_."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

**11. SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

**12. SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (paying for) the research and development. Include address.

**13. ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

**14. KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, rules, and weights is optional.